

# PRODUCT GUIDE

## For Marine Generators





## ALWAYS PRESENT NEVER NOTICED



KOHLER<sub>®</sub> marine generators are smaller. Quieter. With less vibration.\* Each one is built to last and designed to go unnoticed.

Enjoy the journey.

\*Compared to previous KOHLER generator models.



## WHY KOHLER

### PROVEN RELIABILITY

Every KOHLER generator is extensively quality-tested—before model release and before leaving the factory. The result is proven reliability.

### PREMIUM LIMITED WARRANTY

Enjoy full protection throughout the duration of our industry-leading warranty.

### GLOBAL SUPPORT

With nearly 1000 sales and service locations around the world, we're everywhere you go.

Information, specifications, materials and dimensions are subject to change without notice.

## DIESEL GENERATORS

Equipped with either an Advanced Digital Control IId (5 to 11-kW units) or Decision-Maker<sup>®</sup> Controller (12 to 200 kW) and the industry's most acoustically advanced sound shields, KOHLER<sup>®</sup> diesel generators provide the ultimate in overall performance.

### Standard Features

- Remote start connection availability
- Class H insulation
- Multivoltage adjustability
- Voltage regulation of  $\pm 1-2\%$
- Frequency regulation  $\pm 5\%$  droop, .8% steady state for mechanically governed models, .5% isochronous for electronically governed models
- Radio suppression

### Optional Accessories

- Remote start and meter panel kit
- Siphon break
- Remote digital gauge
- Sound shield (depending on model)



55-kW generator with  
DEC 3500 Controller

Information, specifications, materials and dimensions are subject to change without notice.

## DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in)		Weight (Wet) kg (lb)
								H – Housed /	U – Unhoused	
<b>6EKOD</b>	6	60	3	1800	1	120	50	H – 780 (30.7) x 528 (20.8) x 559 (22) U – 743 (29.3) x 448 (17.6) x 536 (21.1)	H – 222 (489) U – 185 (407)	
<b>5EFKOD</b>	5	50		1500		115 / 230	43.4 / 21.7			
						230	21.7			
<b>9EKOZD</b>	8.5	60	3	1800	1	120	70.8	H – 865 (34.1) x 528 (20.8) x 559 (22) U – 827 (32.6) x 448 (17.6) x 536 (21.1)	H – 249 (548) U – 211 (465)	
<b>7EFKOZD</b>	7	50		1500		120 / 240	70.8 / 35.4			
						115 / 230	60.8 / 30.4			
						230	30.4			
<b>11EKOZD</b>	11	60	4	1800	1	120	91.7	H – 960 (37.8) x 528 (20.8) x 559 (22) U – 922 (36.3) x 448 (17.6) x 536 (21.1)	H – 279 (616) U – 241 (532)	
<b>9EFKOZD</b>	9	50		1500		120 / 240	91.7 / 45.8			
						115 / 230	78.3 / 39.1			
						230	39.1			
						240	37.5			
<b>11EKOZD</b>	11	60	4	1800	3	220 / 380	20.9	H – 960 (37.8) x 528 (20.8) x 559 (22) U – 922 (36.3) x 448 (17.6) x 536 (21.1)	H – 406 (896) U – 376 (830)	
<b>9EFKOZD</b>	9	50		1500		240 / 416	19.1			
						120 / 240	33.1			
						127 / 220	36.1			
						230 / 400	16.2			
<b>14EKOZD</b>	14	60	3	1800	1	120	117	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 984 (38.8) x 580 (22.8) x 695 (27.4)	H – 395 (870) U – 376 (830)	
<b>12EFKOZD</b>	12	50		1500		120 / 240	59			
						230	53			
						240	40			

\*kW rating varies by voltage. Consult the generator spec sheet for more detail.

Information, specifications, materials and dimensions are subject to change without notice.



## DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
<b>14EKOZD</b>	14	60	3	1800	3	120 / 208	49	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 984 (38.8) x 580 (22.8) x 695 (27.4)	H – 406 (896) U – 376 (830)
						120 / 240	43		
					1	120 / 240	59		
					3	127 / 220	46		
139 / 240	43								
<b>12EFKOZD</b>	12	50		1500	3	277 / 480	22		
						110 / 190	46		
					1	115 / 230	38		
			3		120 / 208	42			
				230 / 400	22				
			3	240 / 416	21				
220 / 380	23								
<b>16EKOZD</b>	16	60	3	1800	1	120	134	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 1003 (39.5) x 580 (22.8) x 695 (27.4)	H – 406 (896) U – 376 (830)
<b>13.5EFKOZD</b>	14	50				1500	1		
				230	59				
3	240	40							
	<b>16EKOZD</b>	16	60	1800	3	120 / 208	56	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9) U – 1003 (39.5) x 580 (22.8) x 695 (27.4)	H – 395 (870) U – 376 (830)
120 / 240						49			
1					120 / 240	67			
3					127 / 220	53			
					139 / 240	49			
<b>13.5EFKOZD</b>					13.5	50	1500		
	110 / 190	52							
	1	115 / 230	43						
	3	115 / 230	59						
120 / 208		47							
3	230 / 400	25							
	240 / 416	24							
220 / 380	26								

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)		
<b>21EKOZD</b>	21 / 21	60	4	1800	1	120	175	H – 1197 (47.12) x 652.5 (25.69) x 711 (27.99) U – 1121 (44.13) x 577.5 (22.74) x 694 (27.31)	H – 480 (1059) U – 440 (970)		
	21 / 21					120 / 240	88				
<b>18EFKOZD</b>	18 / 18	50		1500	1	230	79				
	14.5 / 14.5					240	61				
<b>21EKOZD</b>	21	60		1800	3	120 / 208	73			H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1121 (44.1) x 577.5 (22.7) x 694 (27.3)	H – 480 (1059) U – 440 (970)
						120 / 240	64				
					1	120 / 240	80				
					3	127 / 220	69				
			139 / 240			64					
			<b>17EFKOZD</b>		17	50	1500	3	277 / 480		
110 / 190	65										
1	115 / 230	54									
3	115 / 230	70									
	120 / 208	58									
230 / 400	31										
240 / 416	29										
220 / 380	33										
<b>24EKOZD</b>	24	60	4	1800	1	120	200	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1138 (44.8) x 577.5 (22.7) x 694 (27.3)	H – 489 (1078) U – 449 (990)		
<b>20.5EFKOZD</b>	21	50				1500	1			120 / 240	100
				230	90						
240	78										

\*kW rating varies by voltage. Consult the generator spec sheet for more detail.  
Information, specifications, materials and dimensions are subject to change without notice.

### DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
24EKOZD	24	60	4	1800	3	120 / 208	84	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1138 (44.8) x 577.5 (22.7) x 694 (27.3)	H – 489 (1078) U – 449 (990)
						120 / 240	73		
					1	120 / 240	92		
					3	127 / 220	79		
3	139 / 240	73							
20.5EFKOZD	20.5	50		1500	3	277 / 480	37		
						110 / 190	78		
						115 / 230	65		
			1		115 / 230	85			
			3	120 / 208	72				
				230 / 400	37				
32EKOZD	32	60	1800	1	120 / 240	133	H – 1303 (51.30) x 661 (26.04) x 778 (30.64) U – 1222 (48.13) x 643 (25.33) x 733 (28.86)	H – 607 (1339) U – 531 (1170)	
					120 / 208	111			
					120 / 240	96			
				1	120 / 240	142			
			3	127 / 220	105				
			3	139 / 240	96				
28EFKOZD	28	50	1500	1	230	122			
					240	96			
				3	110 / 190	106			
					110 / 220	92			
			1	115 / 230	117				
			3	120 / 208	97				
				230 / 400	51				
				240 / 416	49				
				220 / 380	53				

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused / R – Radiator	Weight (Wet) kg (lb)
40EKOZD	40	60	4	1800	1	120 / 240	152	H – 1354 (53.31) x 661 (26.04) x 778 (30.64) U – 1274 (50.17) x 643 (25.33) x 733 (28.86)	H – 637 (1404) U – 567 (1250)
						120 / 208	139		
					3	120 / 240	120		
					1	120 / 240	142		
						127 / 220	131		
					3	139 / 240	120		
						277 / 480	60		
35EFKOZD	35	50		1500	1	230	152		
						240	133		
					3	110 / 190	129		
						110 / 220	112		
				1	115 / 230	130			
				3	120 / 208	121			
					230 / 400	63			
				240 / 416	61				
				220 / 380	65				
			33EFOZDJ	33	50	4	1500	3	110 / 190
	110 / 220	108							
1	115 / 230	143							
	220 / 380	63							
3	230 / 400	60							
	240 / 416	57							

\*kW rating varies by voltage. Consult the generator spec sheet for more detail.  
Information, specifications, materials and dimensions are subject to change without notice.

DIESEL GENERATORS												
Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in)	Weight (Wet) kg (lb)			
								H – Housed / U – Unhoused / R – Radiator				
40EFOZDJ	40	50	4	1500	3	110 / 190	152	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1080 (2380) U – 971 (2140) R – 993 (2190)*			
						110 / 220	131					
						1	115 / 230			174		
						3	220 / 380			76		
						3	230 / 400			72		
						240 / 416	69					
50EFOZDJ	50	50	4	1500	3	110 / 190	190	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1114 (2456) U – 1005 (2216) R – 1028 (2266)*			
						110 / 220	164					
						1	115 / 230			196		
						3	220 / 380			95		
						3	230 / 400			90		
						240 / 416	87					
55EOZDJ	55	60	4	1800	3	120 / 208	191	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*			
						120 / 240	165					
						1	120 / 240			221		
						3	127 / 220			180		
						3	139 / 240			165		
							277 / 480			83		
45EFOZDJ	45	50		1500	3	110 / 190	171			H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*	
						110 / 220	148					
						1	115 / 230					196
						3	220 / 380					86
			3			230 / 400	79					
						240 / 416	71					

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in)	Weight (Wet) kg (lb)			
								H – Housed / U – Unhoused / R – Radiator				
65EOZDJ	65	60	4	1800	3	120 / 208	226	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1125 (2480) U – 1016 (2240) R – 1039 (2290)*			
						120 / 240	195					
						1	120 / 240			221		
						3	127 / 220			213		
						3	139 / 240			195		
							277 / 480			98		
55EFOZDJ	55	50		1500	3	110 / 190	209			H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*	
						110 / 220	181					
						1	115 / 230					217
						3	220 / 380					105
			3			230 / 400	95					
						240 / 416	89					
80EOZDJ	80	60	4	1800	3	120 / 208	278	H – 1754 (69) x 831 (32.7) x 1032 (40.6) U – 1657 (65.2) x 753 (29.6) x 999 (39.3) R – 1992 (78.4) x 890 (35) x 1277 (50.2)	H – 1270 (2800) U – 1148 (2530) R – 1179 (2600)*			
						120 / 240	241					
						127 / 220	262					
						139 / 240	241					
						277 / 480	120					
							110 / 190			266		
70EFOZDJ	70	50		1500	3	110 / 220	230			H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*	
						220 / 380	133					
						230 / 400	126					
						240 / 416	121					

\*kW rating varies by voltage and radiator models. Consult the generator spec sheet for more detail. Information, specifications, materials and dimensions are subject to change without notice.



### DIESEL GENERATORS

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused / R – Radiator	Weight (Wet) kg (lb)
<b>99EOZDJ</b>	99	60	4	1800	3	120 / 208	343	H – 1829 (72) x 831 (32.7) x 1032 (40.6) U – 1732 (68.2) x 753 (29.6) x 999 (39.3) R – 2067 (81.3) x 890 (35) x 1277 (50.2)	H – 1356 (2990) U – 1243 (2740) R – 1275 (2810)*
						120 / 240	298		
						127 / 220	325		
						139 / 240	298		
						277 / 480	149		
<b>80EFOZDJ</b>	80	50	4	1500	3	110 / 190	304		
						110 / 220	262		
						220 / 380	152		
						230 / 400	144		
						240 / 416	139		
<b>125EOZDJ</b>	125	60	6	1800	3	120 / 208	434	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2068 (81.4) x 893 (35.2) x 1003 (39.5) R – 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H – 1683 (3710) U – 1515 (3340) R – 1578 (3478)
						120 / 240	376		
						127 / 220	410		
						139 / 240	376		
<b>100EFOZDJ</b>	100	50	6	1500	3	277 / 480	188		
						110 / 190	380		
						120 / 208	347		
						110 / 220	328		
						220 / 380	190		
						230 / 400	180		
240 / 416	173								

Model	kW*	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in) H – Housed / U – Unhoused / R – Radiator	Weight (Wet) kg (lb)
<b>150EOZDJ</b>	150	60	6	1800	3	120 / 208	520	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2091 (82.3) x 893 (35.2) x 1003 (39.5) R – 2498 (98) x 1129 (44.5) x 1275 (50.2)	H – 1719 (3789) U – 1551 (3419) R – 1613 (3557)
						120 / 240	451		
						127 / 220	492		
						139 / 240	451		
						277 / 480	228		
<b>125EFOZDJ</b>	125	50	6	1500	3	110 / 190	474		
						120 / 208	433		
						110 / 220	409		
						220 / 380	237		
						230 / 400	225		
						240 / 416	217		
<b>200EOZDJ</b>	200	60	6	1800	3	120 / 208	694	H – 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U – 2490 (98) x 970 (38.2) x 1086 (42.8)	H – 2147 (4733) U – 2067 (4558)
						120 / 240	601		
						127 / 220	656		
						139 / 240	601		
						277 / 480	301		
<b>175EFOZDJ</b>	175	50	6	1500	3	110 / 190	665		
						110 / 220	574		
						120 / 208	607		
						220 / 380	332		
						230 / 400	316		
						240 / 416	304		

\*kW rating varies by voltage and radiator models. Consult the generator spec sheet for more detail. Information, specifications, materials and dimensions are subject to change without notice.





# GLOBAL SUPPORT

With nearly 1000 sales and service locations all over the world, we're everywhere you go.

**AMERICAS  
CARIBBEAN**  
+1 920 565 3381  
+1 800 544 2444  
FAX +1 920 459 1646

**CHINA**  
+86 21 26062169  
+86 400 1808 900

**EUROPE  
MIDDLE EAST  
AFRICA**  
+31 168 331630  
FAX +31 168 331631

**ASIA PACIFIC**  
+65 6660 2681  
FAX +65 6264 6455

**NEW ZEALAND  
AUSTRALIA**  
+61 88 29 02100

**INDIA**  
+91 80 42867000  
FAX +91 80 23615972



**KOHLERPOWER.COM**

Printed in U.S.A. G12-480 06/18 © 2018 by Kohler Co.

